

10/214,083

PGPUB-DOCUMENT-NUMBER: 20030086526

PGPUB-FILING-TYPE: new

DOCUMENT-IDENTIFIER: US 20030086526 A1

TITLE: System and method for positioning an
electronic portal imaging device

PUBLICATION-DATE: May 8, 2003

INVENTOR-INFORMATION:

NAME	CITY	STATE
COUNTRY RULE-47		
Clark, Charles	Pleasanton	CA
US		
Lentz, Loren	Pleasanton	CA
US		
Penny, Debra	Livermore	CA
US		
Gibb, William J.	San Anselmo	CA
US		
Steinberg, Todd H.	Antioch	CA
US		

US-CL-CURRENT: 378/64, 378/65

CLAIMS:

What is claimed is:

1. A portal imaging device positioning apparatus attachable to a radiation therapy device gantry, comprising: a support attachable to said gantry; a vertically-adjustable portal imaging device positioner attachable to said support, said portal imaging device positioner operable in a first mode and a second mode, wherein in said first mode said portal imaging device positioner maintains an imaging panel in position to receive radiation passing through a body maintained in a patient plane, and wherein in said second mode portal imaging device positioner maintains said imaging panel to receive radiation substantially at said patient plane; and a graphical user

interface adapted to
control deployment of said portal imaging device positioner.

2. A portal imaging device positioning apparatus according to claim 1, said graphical user interface adapted to display movements of said portal imaging device positioner and said gantry.

3. A portal imaging device positioning apparatus according to claim 2, further including a controller adapted to define a boundary for an radiation field and determine if an extent of said boundary exceeds an extent of a boundary of an imaging area.

4. A portal imaging device positioning apparatus according to claim 1, said graphical user interface adapted to allow a user to adjust a position of the imaging panel using buttons with symbols labeled to indicate a direction of motion.

5. A portal imaging device positioning apparatus according to claim 4, said graphical user interface adapted to store multiple configurations of said imaging panel and automatically move the imaging panel to the stored configuration.

6. A radiation therapy device, comprising: a linear accelerator for providing radiation to a body; and an electronic portal imaging device operably coupled to said linear accelerator; and a control unit including a user interface and adapted to control deployment of an imaging panel of said electronic portal imaging device from a substantially vertical position to a substantially horizontal position.

7. A radiation therapy device according to claim 6, said user interface adapted to allow a user to adjust a position of the imaging panel using buttons labeled with symbols to indicate a direction of motion.

8. A radiation therapy device according to claim 7, said

control unit adapted
to store multiple configurations of said imaging panel and
automatically move
the imaging panel to the stored configuration.

9. A radiation therapy device according to claim 6, further
including a
controller adapted to define a boundary for a radiation field
and determine if
an extent of said boundary exceeds an extent of a boundary of an
imaging area.

10. A radiation therapy device according to claim 9, said
control unit adapted
to interface to a gantry control unit and display using said
graphical user
interface motions of said gantry and said portal imaging device.

11. A method for providing a portal imaging device positioning
apparatus
attachable to a radiation therapy device gantry, comprising:
providing a
support attachable to said gantry; providing a
vertically-adjustable portal
imaging device positioner attachable to said support, said
portal imaging
device positioner operable in a first mode and a second mode,
wherein in said
first mode said portal imaging device positioner maintains an
imaging panel in
position to receive radiation passing through a body maintained
in a patient
plane, and wherein in said second mode portal imaging device
positioner
maintains said imaging panel to receive radiation substantially
at said patient
plane; and providing a graphical user interface adapted to
control deployment
of said portal imaging device positioner.

12. A method according to claim 11, said graphical user
interface adapted to
display movements of said portal imaging device positioner and
said gantry.

13. A method according to claim 12, further including providing
a controller
adapted to define a boundary for a radiation field and determine
if an extent
of said boundary exceeds an extent of a boundary of an imaging
area.

14. A method according to claim 11, said graphical user interface adapted to allow a user to adjust a position of the imaging panel using buttons with symbols labeled to indicate a direction of motion.

15. A method according to claim 14, said graphical user interface adapted to store multiple configurations of said imaging panel and automatically move the imaging panel to the stored configuration.

10/053, 283

PGPUB-DOCUMENT-NUMBER: 20030086529

PGPUB-FILING-TYPE: new

DOCUMENT-IDENTIFIER: US 20030086529 A1

TITLE: System and method for positioning an
electronic portal imaging device

PUBLICATION-DATE: May 8, 2003

INVENTOR-INFORMATION:

NAME	CITY	STATE
COUNTRY RULE-47		
Clark, Charles	Pleasanton	CA
US		
Lentz, Loren	Pleasanton	CA
US		
Penny, Debra	Livermore	CA
US		
Gibb, William J.	San Anselmo	CA
US		
Steinberg, Todd H.	Antioch	CA
US		

US-CL-CURRENT: 378/65, 378/205

CLAIMS:

What is claimed is:

1. A portal imaging device positioning apparatus attachable to a radiation therapy device gantry, comprising: a support attachable to said gantry; and a vertically-adjustable portal imaging device positioner attachable to said support, said portal imaging device positioner operable in a first mode and a second mode, wherein in said first mode said portal imaging device positioner maintains an imaging panel in position to receive radiation passing through a body maintained in a patient plane, and wherein in said second mode portal imaging device positioner maintains said imaging panel to receive radiation substantially at said patient plane.

2. A portal imaging device positioning apparatus according to claim 1, said vertically-adjustable portal imaging device positioner including: a vertical drive unit adjustably attachable at a mounting cavity to said support; and a mounting unit adjustably attachable to said vertical drive unit, and adapted to deploy said imaging panel from a vertical position to a horizontal position.

3. A portal imaging device positioning apparatus according to claim 2, wherein said vertical drive unit is adjustable in said first mode such that a top of said support is substantially adjacent a top of said mounting cavity, and adjustable in said second mode such that a bottom of said support is substantially adjacent a bottom of said mounting cavity.

4. A portal imaging device positioning apparatus according to claim 3, wherein said imaging panel is adapted to be temporarily secured to said support during an adjustment from said first mode to said second mode.

5. A portal imaging device positioning method, comprising: adjusting an imaging panel operably secured to a radiation therapy device gantry from a first position in a first mode below a patient plane to a second position in a second mode at a patient plane.

6. A method according to claim 5, said adjusting comprising: temporarily securing a vertically positioned imaging panel to a support; temporarily unsecuring a main drive assembly from said support; adjusting said main drive assembly to said second position; re-securing said main drive assembly; and unsecuring said vertically positioned imaging panel.

7. A method according to claim 6, said adjusting comprising: adjusting said vertical drive unit in said first mode such that a top of said support is substantially adjacent a top of a mounting cavity on said vertical drive unit;

and adjusting said vertical drive unit in said second mode such that a bottom of said support is substantially adjacent a bottom of said mounting cavity.

8. A method according to claim 7, further comprising horizontally deploying said imaging panel after said imaging panel has been adjusted to said second position.

9. A portal imaging system, comprising: a radiation delivery apparatus; and means for deploying an imaging panel in a first mode to receive radiation from said apparatus below a patient plane and in a second mode at said patient plane.

10. A system according to claim 9, said deploying means comprising: a vertical drive unit adjustably attachable at a mounting cavity to a support; and a mounting unit adjustably attachable to said vertical drive unit, and adapted to deploy said imaging panel from a vertical position to a horizontal position.

11. A system according to claim 10, wherein said deploying means further comprises means for adjusting said vertical drive unit in said first mode such that a top of said support is substantially adjacent a top of said mounting cavity, and in said second mode such that a bottom of said support is substantially adjacent a bottom of said mounting cavity.

12. A system according to claim 11, comprising: means for temporarily securing said imaging panel to said support; and means for temporarily unsecuring a main drive assembly from said support.

13. A portal imaging device method, comprising: providing a support attachable at a first end to a treatment gantry; and providing a vertically-adjustable portal imaging device positioner, said portal imaging device positioner operable in a first mode and a second mode, wherein in said first mode said

portal imaging device positioner maintains an imaging panel in position to receive radiation through a body maintained in a patient plane, and wherein in said second mode portal imaging device positioner maintains said imaging panel to receive radiation at said patient plane.

14. A method according to claim 13, said vertically-adjustable portal imaging device positioner including: a vertical drive unit adjustably attachable at a mounting cavity to said support; and a mounting unit adjustably attachable to said vertical drive unit, and adapted to deploy said imaging panel from a vertical position to a horizontal position.

15. A method according to claim 14, wherein said vertical drive unit is adjustable in said first mode such that a top of said support is substantially adjacent a top of said mounting cavity, and adjustable in said second mode such that a bottom of said support is substantially adjacent a bottom of said mounting cavity.

16. A method according to claim 15, wherein said imaging panel is adapted to be temporarily secured to said support during an adjustment from said first mode to said second mode.